

TY2503 TY4003

½”–3” AUTO-FEED ATTACHMENT



APPLICATIONS

Metal to metal, metal roofing & siding, metal decking, subfloor sheathing, and decking.

FEATURES AND BENEFITS

- “Feed on return” functionality; puts the screw in line before you drive
- Adjustable Depth-of-Drive
- Powerful 5.4 amp motor
- TY2503: 2500 RPM speed for higher torque applications and applications that require slower speeds
- TY4003: 4000 RPM speed for higher speed applications

TY2503 Item Number T032001

TY4003 Item Number T033001

FASTENERS

Screw Lengths: ½”–3”; **Screw Diameters:** #6–#12

Application	Length	Screw Series
Drywall to Wood	1¼”, 1⅝”, 2”	GCS Series
Cement Board to Steel	1¼”, 2”	CHND Series
Cement Board to Steel	1½”	CFDD Series
Decking	1¾”, 2”, 2½”, 3”	DCTD Series
Underlayment	1¼”	UHS Series
Subfloor and Sheathing	1½”, 1¾”, 2”, 2½”, 3”	SCS Series
AdvanTech to Wood	2”	SHS Series
Sheathing to Steel	1¼”, 1⅝”, 2”, 2½”, 3”	SFW Series
Metal Attachment	¾”, 1¼”	MDFXY Series
Metal Framing	½”	MFSPP Series