

## TY5100

### HIGH-SPEED, CORDED AUTO-FEED SCREWDRIVER

**Patented Corner-Fit Nose**  
The TyRex Corner-Fit nose is the only design on the market that retracts into the integrated tool housing, enabling users to fasten into corners. Ideal for drywall and window installations.

**“Reverse-Alert” Feature**  
Unlike other tools with reversible functions, the TY5100’s design makes it impossible for the operator to inadvertently switch from “drive” to “reverse” mode. Red indicator tag signals when tool is in “reverse”.

**Adjustable Depth of Drive**  
Drive-depth can be adjusted by turning thumb wheel; window allows for easy viewing of setting.

**One-Hand Bit Release**  
Bits are released and drop out at the touch of a button. Plus on-board storage of an extra bit saves time on the job.

**Patented Clutch Design**  
Bit wear and fastener overdriving is eliminated by the TY5100’s patented clutch design, which disengages when screw is sufficiently set.

**High-Speed Motor**  
For increased productivity.

**Lightweight, Balanced Design**  
Weighing less than five pounds, the TY5100 features a sleek profile, offering an excellent sight line for accurate placement of fasteners.

**Variable-Speed Trigger**  
From zero to 5000 rpm and back, the trigger permits “feathering” of fasteners for improved control. Trigger-lock button allows for constant operation in high-volume installations.

**Trigger Lock**  
For continuous work.

**Industrial-Strength Cord**  
10-foot cord is heavy-duty, professional grade rubber, not vinyl/plastic as found on many other electric tools.

# 5000 RPM

### FEATURES AND BENEFITS

- New higher-speed tool for increased productivity
- Fully integrated (no attachments) design for better balance, smoother operation, and less user fatigue
- Patented Corner-Fit™ feed system allows for placement of screws in corners and around obstructions
- Patented Clutch Design-no more stripped out heads and improved bit life
- Variable-Speed Trigger and Adjustable Depth-of-Drive for precision fastening
- One-Hand Bit Release-makes bit change out quick
- 10ft. Industrial Strength Cord
- Comes with bits and nosepiece wrench “on board”

### TOOL SPECIFICATIONS

<b>RPM</b>	0-5000
<b>Current</b>	4.3 amps
<b>Weight</b>	4.8 lbs
<b>Height</b>	8"
<b>Length</b>	15 <sup>3</sup> / <sub>4</sub> "
<b>Width</b>	3"
<b>Item Number</b>	T022001 BOX

### APPLICATIONS

Drywall / DensGlass®, sheathing, cement board, underlayment, crating / pallet manufacturing.

### FASTENERS

**Screw Lengths:** 1" – 2"  
**Screw Diameters:** #6 – #8

Application	Length	Screw Series
Drywall to Wood	1 <sup>1</sup> / <sub>4</sub> ", 1 <sup>5</sup> / <sub>8</sub> ", 2"	†GCS Series
Drywall to Steel	1 <sup>1</sup> / <sub>4</sub> ", 1 <sup>5</sup> / <sub>8</sub> ", 2"	†GFD Series
Drywall to Steel	1 <sup>1</sup> / <sub>4</sub> ", 1 <sup>5</sup> / <sub>8</sub> "	GFS Series
Cement Board to Steel	1 <sup>1</sup> / <sub>4</sub> ", 2"	CHND Series
Underlayment	1 <sup>1</sup> / <sub>4</sub> "	UHS Series
Cement Board to Steel	1 <sup>1</sup> / <sub>2</sub> "	CFDD Series
Window and Steel	1 <sup>1</sup> / <sub>4</sub> "	**MCTAQZB Series
Sheathing to Steel or Wood	1 <sup>1</sup> / <sub>2</sub> "	SFS Series
Subfloor and Sheathing	1 <sup>1</sup> / <sub>2</sub> ", 1 <sup>3</sup> / <sub>4</sub> ", 2"	SCS Series
Metal to Metal	1 <sup>1</sup> / <sub>4</sub> "	†MFDAQZK Series

\*\* NPC010 is recommended for vinyl window applications.

† NPC021 is required to drive these screws.